



Toll Free: 87 PERMATEX  
(877-376-2839)

10 Columbus Blvd., Hartford,  
Connecticut 06106

6875 Parkland Boulevard, Solon  
Ohio 44139

## Technical Data Sheet

### NOS<sup>®</sup> Max Street<sup>™</sup> Octane Booster

AAM Revised 10/07

#### PRODUCT DESCRIPTION

NOS<sup>®</sup> Max Street<sup>™</sup> Octane Booster was designed for most passenger vehicles. It was developed to increase octane effect ratings up to 3 full octane Numbers or 30 Points (1 Octane Number = 10 Points). It is formulated to eliminate the pre-ignition (pinging) common to lower octane gasoline, and helps in all situations from pulling a load up a steep grade to racing with nitrous oxide at the track.

#### PRODUCT BENEFITS

- Safe for oxygen sensors and catalytic converters
- Increases octane effect of unleaded gasoline up to 3 full Octane Numbers
- Cleans fuel injectors and combustion chamber
- Excellent as a lead substitute
- Reduces hydrocarbon and carbon monoxide emissions
- EPA registered
- Provides corrosion protection
- Improves fuel efficiency
- Prevents valve sticking
- Eliminates engine knocking and pinging
- Restores lost horsepower
- Prevents stalling and hesitation
- Water suppressant properties

#### TYPICAL APPLICATIONS

- Recommended for all standard carbureted, fuel injected, turbo and super-charged engines
- Excellent smoke suppressant for 2 cycle engines
- Recommended for high-performance engines plus marine, industrial, lawn, farm and recreational vehicles

NOTE: NOT recommended for use in diesel engines

#### DIRECTIONS FOR USE

1. Add the contents of bottle to at least 16 gallons of gasoline.
2. Remove cap and pour entire contents into fuel tank into fuel tank. If spilled onto painted surface, wipe off immediately.
3. Replace cap after use and dispose of bottle and any contaminated rags or towels in accordance with all federal, state and local regulations; never expose product directly or indirectly to sunlight.
4. NOTE: Never expose liquid product to direct or indirect sunlight.

#### For Cleanup

1. Wipe off any spilled fluid with a dry cloth.
2. Clean hands with Permatex<sup>®</sup> Fast Orange<sup>®</sup> hand cleaner or soap and water.

#### PHYSICAL PROPERTIES

	Typical Value
Chemical Type	Hydrocarbon blend, special additives
Appearance	Pale liquid
Odor	Slight hydrocarbon odor

#### GENERAL INFORMATION

**This product is not recommended for use in pure oxygen and/or oxygen rich systems.**

**For safe handling information on this product, consult the Material Safety Data Sheet, (MSDS).**

#### ORDERING INFORMATION

Part Number	Container Size
12003	16 Fl. oz. bottle

#### STORAGE

Products shall be ideally stored in a cool, dry location in unopened containers at a temperature between 8° and 28°C (46° and 82°F) unless otherwise labeled. Optimal storage is at the lower half of this temperature range. To prevent contamination of unused product, do not return any material to its original container.

#### NOTE

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. **ITW Permatex, Inc. specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Permatex, Inc. products and disclaims any liability for consequential or incidental damages of any kind, including lost profits.** This product may be covered by one or more United States or foreign patents or patent applications.

NOT FOR PRODUCT SPECIFICATIONS.  
THE TECHNICAL DATA CONTAINED HEREIN ARE INTENDED AS REFERENCE ONLY.  
PLEASE CONTACT PERMATEX, INC., TECHNICAL SERVICE DEPARTMENT FOR ASSISTANCE AND RECOMMENDATIONS FOR YOUR SPECIFIC APPLICATION.  
PERMATEX, INC., HARTFORD SQUARE NORTH, 10 COLUMBUS BOULEVARD, HARTFORD, CT 06106 PHONE - (1-877)PERMATEX