



710 2T

High Performance 2 stroke engine lubricant

Lubrication by oil injector or premix

100% Synthetic – Ester – Anti-Smoke

TYPE OF USE

Any high performance 2 stroke bike, sports bikes, replicas, trails, off road bikes, enduro, mopeds... fitted with high performance 2 stroke engines, running at high rpm in severe conditions, direct injection or carburettor.

Suitable for oil injector systems or premix, leaded or unleaded gasoline

Compatible with catalytic converters.

Other uses : Scooters, ATV...

PERFORMANCE

STANDARDS

API TC – JASO FC - ISO-L-EGD

APPROVAL

JASO FD under N°033MOT064

100% synthetic lubricant, Ester technology, specially engineered for high performance engines running at high rpm, perfect oil film resistance to protect against wear.

Improved power output, minimise engine internal friction :

Japanese JASO standard consists in passing 4 engine bench tests in order to evaluate lubricity, detergency, anti smoke and anti deposit lubricant properties. JASO FD performance is the highest level of JASO standard, improved engine cleanliness compared to JASO FC.

Formulation built on synthetic bases with very high combustion properties which minimise smoke and deposits.

Instantaneous and stable mixing with gasoline.

RECOMMENDATIONS

Mixing ratio: from 2% to 4% (from 50:1 to 25:1) according to manufacturers' requirements.

Adjust according to your own use.

PROPERTIES

Colour	Visual	Green.
Density at 20°C (68°F)	ASTM D1298	0.862
Viscosity at 100°C (212°F)	ASTM D445	8.9 mm ² /s
Viscosity at 40°C (104°F)	ASTM D445	46.4 mm ² /s
Viscosity index	ASTM D2270	175
Flash point	ASTM D92	88°C / 190°F
TBN	ASTM D 2896	2.15 mg KOH/g

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

8373

Product specifications are not definitive from the order which is subject to our general conditions of sale and warranty. – Made in France

MOTUL . 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 - Tel 33 1 48 11 70 00 - FAX 33 1 48 33 28 79 . Site Web : www.motul.fr

10/05